



Conforms to Hazardous Products Regulation SOR/2015-17 (as amended by SOR/2022-272)

SAFETY DATA SHEET

Wipeout for Brick Surfaces

SECTION 1: IDENTIFICATION

1.1. Product identifier

Trade name: Wipeout for Brick Surfaces

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture: Paint and varnish remover - Graffiti remover

Uses advised against : None known.

1.3. Details of the supplier of the safety data sheet

Company and address: Off The Walls
754 Francis Road
L7T 4A3 Burlington
Canada
1-905-632-9849

Contact person: Technical Department

E-mail: Technical Department

SDS date: 2026-04-23

SDS Version: 2.0

Date of previous version: 2025-11-19 (2.0)

1.4. Emergency telephone number

613-996-6666, 24 Hours

SECTION 2: HAZARD(S) IDENTIFICATION

Classified as hazardous according to Hazardous Products Regulation SOR/2015-17 (as amended by SOR/2022-272).

2.1. Classification of the substance or mixture

Flam. Liq. 3; H226, Flammable liquid and vapour.

Acute Tox. 4; H302, Harmful if swallowed.

Skin Corr. 1A; H314, Causes severe skin burns and eye damage.

Eye Dam. 1; H318, Causes serious eye damage.

2.2. Label elements

Hazard pictogram(s):



Signal word:

Danger

Hazard statement(s):

Flammable liquid and vapour. (H226)

Harmful if swallowed. (H302)

Causes severe skin burns and eye damage. (H314)

Precautionary statement(s):

General:

If medical advice is needed, have product container or label at hand. (P101)

Keep out of reach of children. (P102)

Prevention:

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. (P210)

Do not breathe vapour/mist. (P260)

Do not eat, drink or smoke when using this product. (P270)

Wear eye protection/protective gloves/protective clothing. (P280)

Response:

IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell. (P301+P312)

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. (P301+P330+P331)

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. (P303+P361+P353)

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. (P305+P351+P338)

Immediately call a POISON CENTER/doctor. (P310)

In case of fire: Use water mist/carbon dioxide/alcohol-resistant foam to extinguish. (P370+P378)

Storage:

Store in a well-ventilated place. Keep cool. (P403+P235)

Store locked up. (P405)

Disposal:

Dispose of contents/container in accordance with local regulation.

(P501)

Hazardous substances:

benzyl alcohol

potassium hydroxide;caustic potash

D-Glucopyranose, oligomers, decyl octyl glycosides

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substances

Not applicable. This product is a mixture.

3.2. Mixtures

Chemical name	Common name/synonyms	Identifiers	% w/w	Classification	Note
benzyl alcohol		CAS No.: 100-51-6	15-25%	Acute Tox. 4, H302 Eye Irrit. 2, H319 Acute Tox. 4, H332	
1-methoxy-2-propanol;monopropylene glycol methyl ether		CAS No.: 107-98-2	15-25%	Flam. Liq. 3, H226 STOT SE 3, H336 (SCL: 100.00 %)	
potassium hydroxide;caustic potash		CAS No.: 1310-58-3	10-15%	Met. Corr. 1, H290 Acute Tox. 4, H302 Skin Corr. 1A, H314 Eye Dam. 1, H318	
D-Glucopyranose, oligomers, decyl octyl glycosides		CAS No.: 68515-73-1	5-10%	Eye Dam. 1, H318	[19]

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

Other information

[19] UVCB = Unknown or variable composition, complex reaction products or of biological materials

SECTION 4: FIRST-AID MEASURES

4.1. ▼ Description of first aid measures

General information:

If breathing is irregular, drowsiness, loss of consciousness or cramps: Call 911 and give immediate treatment (first aid).

Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

Inhalation:

Upon breathing difficulties or irritation of the respiratory tract: Bring the person into fresh air and stay with him/her.

Skin contact:

Flush exposed area with water for a long time - at least 30 minutes. It may be necessary to flush for several

hours. Use a comfortable water temperature (20-30 °C). Contact Poison Information/doctor/hospital for further advice on follow-up and treatment.

Remove contaminated clothing and shoes immediately. Ensure to wash exposed skin thoroughly with water and soap. Skin cleanser can be used. DO NOT use solvents or thinners.

If skin irritation occurs: Get medical advice/attention.

▼ *Eye contact:*

If in eyes: Flush eyes with plenty of water or saline solution (20-30 °C) for at least 30 minutes and continue until irritation stops. Remove contact lenses. Make sure you flush under the upper and lower eyelids. Seek medical assistance immediately and continue flushing during transport.

Ingestion:

In the case of ingestion, contact a doctor immediately. If the person is conscious, give them water. DO NOT try to induce vomiting unless this is recommended by a doctor. Hold head facing down to prevent vomit from returning to the mouth and throat. Prevent shock by keeping the injured person warm and calm. Initiate immediate resuscitation if breathing stops. If unconscious, roll the injured person into recovery position. Call an ambulance.

Burns:

Rinse with water until pain stops then continue to rinse for 30 minutes.

4.2. Most important symptoms and effects, both acute and delayed

Tissue-damaging effects: This product contains substances with skin corrosive properties. Inhaled vapour or aerosols may produce adverse effects to lungs, irritations and burns in the respiratory organs as well as coughing. Dermal contact and contact with the eye cause irreversible effects.

4.3. Indication of any immediate medical attention and special treatment needed

IF exposed or concerned:

Get immediate medical advice/attention.

Information to medics

Bring this safety data sheet or the label from this product.

SECTION 5: FIRE-FIGHTING MEASURES

5.1. Extinguishing media

Suitable extinguishing media: Alcohol-resistant foam, carbon dioxide, powder, water mist.
Unsuitable extinguishing media: Waterjets should not be used, since they can spread the fire.

5.2. Special hazards arising from the substance or mixture



Conforms to Hazardous Products Regulation SOR/2015-17 (as amended by SOR/2022-272)

Flammable liquid and vapour.

In use may form flammable/explosive vapour-air mixture.

Fire will result in dense smoke. Exposure to combustion products may harm your health.

Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

If the product is exposed to high temperatures, e.g. in the event of fire, dangerous decomposition compounds are produced. These are:

Nitrogen oxides (NO_x)

Carbon oxides (CO / CO₂)

Some metal oxides

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact a poison centre in order to obtain further advice. See section 1 "Emergency telephone number".

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Storages not yet ignited must be cooled by water mist. Remove flammable materials if conditions allow it. Ensure sufficient ventilation.

Avoid direct contact with spilled substances.

Ensure adequate ventilation, especially in confined areas.

Contaminated areas may be slippery.

6.2. Environmental precautions

Avoid discharge to lakes, streams, sewers, etc.

Keep unauthorized persons away from the spill

6.3. Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

Wherever possible cleaning should be performed with normal cleaning agents. Avoid use of solvents.

6.4. Reference to other sections

See section 13 "Disposal considerations" on handling of waste.

See section 8 "Exposure controls/personal protection" for protective measures.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Ground and bond container and receiving equipment.

Use explosion-proof electrical/lighting/ventilating equipment.

Use non-sparking tools.



Take action to prevent static discharges.
Avoid direct contact with the product.
Avoid contact during pregnancy and while nursing.
Smoking, drinking and consumption of food is not allowed in the work area.
See section 8 "Exposure controls/personal protection" for information on personal protection.

7.2. Conditions for safe storage, including any incompatibilities

Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

Take action to prevent static discharges.

Must be stored in a cool and well-ventilated area, away from possible sources of ignition.

Recommended storage material: Always store in containers of the same material as the original container.

Storage conditions: Store in a closed container

Incompatible materials: Acids
Strong oxidizing agents
Reducing agents
Some metals

7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

ALBERTA

1-methoxy-2-propanol;monopropylene glycol methyl ether

Long term exposure limit (8 hours) (ppm): 100

Long term exposure limit (8 hours) (mg/m³): 369

Short term exposure limit (15 minutes) (ppm): 150

Short term exposure limit (15 minutes) (mg/m³): 553

potassium hydroxide;caustic potash

Short term exposure limit (15 minutes) (mg/m³): (c) 2

Annotations:

3 = Occupational exposure limit is based on irritation effects and its adjustment to compensate for unusual work schedules is not required.

Occupational Health and Safety Code 2009 Order, Alta Reg 87/2009 (revised in 2018)

BRITISH COLUMBIA

1-methoxy-2-propanol;monopropylene glycol methyl ether

Time-Weighted Average Limit (TWA): 50 ppm



Conforms to Hazardous Products Regulation SOR/2015-17 (as amended by SOR/2022-272)

Short-Term Exposure Limit (STEL) / Ceiling Limit (C): 100 ppm
potassium hydroxide;caustic potash
Short-Term Exposure Limit (STEL) / Ceiling Limit (C): C 2 mg/m³
OHS Regulation Part 5: Chemical Agents and Biological Agents.

ONTARIO

1-methoxy-2-propanol;monopropylene glycol methyl ether
Time-Weighted Average Limit (TWA): 50 ppm
Short-Term Exposure Limit (STEL) / Ceiling Limit (C): 100 ppm
potassium hydroxide;caustic potash
Short-Term Exposure Limit (STEL) / Ceiling Limit (C): C 2 mg/m³
Regulation 833 (Control of Exposure to Biological or Chemical Agents) and Ontario
Regulation 490/09 (Designated Substances)

QUEBEC

1-methoxy-2-propanol;monopropylene glycol methyl ether
Long term exposure limit (8 hours) (ppm): 100
Long term exposure limit (8 hours) (mg/m³): 369
potassium hydroxide;caustic potash
Annotations:
EM = Exposure must be reduced to a minimum in accordance with section 42.
RP = A substance which may not be recirculated in accordance with section 108.
Regulation respecting occupational health and safety (Chapter S-2.1, r. 13)

SASKATCHEWAN

1-methoxy-2-propanol;monopropylene glycol methyl ether
Long term exposure limit (8 hours) (ppm): 100
Short term exposure limit (15 minutes) (ppm): 150
potassium hydroxide;caustic potash
STEV/Ceiling (mg/m³): 2
The Occupational Health and Safety Regulations, 2020, Chapter S15.1 Reg 10.

8.2. Exposure controls

Compliance with the given occupational exposure limits values should be controlled on a regular basis.

<i>General recommendations:</i>	Smoking, drinking and consumption of food is not allowed in the work area.
<i>Exposure scenarios:</i>	There are no exposure scenarios implemented for this product.
<i>Exposure limits:</i>	Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.
<i>Appropriate technical measures:</i>	The formation of vapours must be kept at a minimum and below current limit values (see above). Installation of



Conforms to Hazardous Products Regulation SOR/2015-17 (as amended by SOR/2022-272)

a local exhaust system if normal air flow in the work room is not sufficient is recommended. Ensure eyewash and emergency showers are clearly marked.

Ensure that eyewash stations and safety showers are located within easy reach.

Apply standard precautions during use of the product. Avoid inhalation of vapours.

Hygiene measures:

In between use of the product and at the end of the working day all exposed areas of the body must be washed thoroughly. Pay special attention to hands, forearms and face.

Measures to avoid environmental exposure:

Keep damming materials near the workplace. If possible, collect spillage during work.

Individual protection measures, such as personal protective equipment

Generally:

No specific requirements.

Respiratory Equipment:

Use local exhaust or dilution ventilation

Skin protection:

Wear chemical protective clothing e.g. gloves, aprons, boots.

Hand protection:

Chemical Resistant, impervious gloves

Eye protection:

Wear chemical safety goggles and face shield when contact is possible.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

<i>Physical state:</i>	Liquid
<i>Colour:</i>	Clear, Colourless
<i>Odour:</i>	Faint
<i>Odour threshold (ppm):</i>	No data available
<i>pH:</i>	13-14
<i>Density (g/cm³):</i>	-
<i>Relative density:</i>	1.15
<i>Kinematic viscosity:</i>	No data available
<i>Particle characteristics:</i>	No data available

Phase changes

<i>Melting point/Freezing point (°C):</i>	No data available
---	-------------------



Conforms to Hazardous Products Regulation SOR/2015-17 (as amended by SOR/2022-272)

<i>Softening point/range (°F):</i>	Does not apply to liquids.
<i>Boiling point (°C):</i>	No data available
<i>Vapour pressure:</i>	No data available
<i>Relative vapour density:</i>	No data available
<i>Decomposition temperature (°C):</i>	No data available

Data on fire and explosion hazards

<i>Flash point (°C):</i>	40
<i>Flammability (°C):</i>	The material is ignitable.
<i>Auto-ignition temperature (°C):</i>	No data available
<i>Explosion limits (% v/v):</i>	No data available

Solubility

<i>Solubility in water:</i>	Soluble
<i>n-octanol/water coefficient (LogKow):</i>	No data available
<i>Solubility in fat (g/L):</i>	No data available

9.2. Other information

<i>Evaporation rate (n-butylacetate = 100):</i>	No data available
<i>Other physical and chemical parameters:</i>	No data available.
<i>Oxidizing properties:</i>	No data available

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

No data available.

10.2. Chemical stability

The product is stable under the conditions, noted in section 7 "Handling and storage".

10.3. Possibility of hazardous reactions

None known.

10.4. Conditions to avoid

Avoid static electricity.

10.5. Incompatible materials

Acids
Some metals
Reducing agents
Strong oxidizing agents



Conforms to Hazardous Products Regulation SOR/2015-17 (as amended by SOR/2022-272)

10.6. Hazardous decomposition products

Thermal decomposition may produce corrosive vapours.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Acute toxicity

Harmful if swallowed.

Skin corrosion/irritation

Causes severe skin burns and eye damage.

Serious eye damage/irritation

Causes serious eye damage.

▼ Respiratory sensitisation

Based on available data, the classification criteria are not met.

▼ Skin sensitisation

Based on available data, the classification criteria are not met.

▼ Germ cell mutagenicity

Based on available data, the classification criteria are not met.

▼ Carcinogenicity

Based on available data, the classification criteria are not met.

▼ Reproductive toxicity

Based on available data, the classification criteria are not met.

▼ STOT-single exposure

Based on available data, the classification criteria are not met.

▼ STOT-repeated exposure

Based on available data, the classification criteria are not met.

▼ Aspiration hazard

Based on available data, the classification criteria are not met.

Long term effects

Tissue-damaging effects: This product contains substances with skin corrosive properties. Inhaled vapour or aerosols may produce adverse effects to lungs, irritations and burns in the respiratory organs as well as coughing. Dermal contact and contact with the eye cause irreversible effects.

Other information

None known.

SECTION 12: ECOLOGICAL INFORMATION

12.1. ▼ Toxicity

Conforms to Hazardous Products Regulation SOR/2015-17 (as amended by SOR/2022-272)

Based on available data, the classification criteria are not met.

12.2. ▼ Persistence and degradability

Based on available data, the classification criteria are not met.

12.3. ▼ Bioaccumulative potential

Based on available data, the classification criteria are not met.

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification.

12.6. Other adverse effects

None known.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste treatment methods

None of the components are listed

Specific labelling

Contaminated packing

Packaging containing residues of the product must be disposed of similarly to the product.

SECTION 14: TRANSPORT INFORMATION

	14.1 UN / ID	14.2 UN proper shipping name	14.3 Hazard class(es)	14.4 PG*	14.5 Env**	Other information:
TDG	UN2924	FLAMMABLE LIQUID, CORROSIVE, N.O.S. (potassium hydroxide;caustic potash, 1-methoxy-2- propanol;monopropylene glycol methyl ether)	Transport hazard class: 3 Label: 3+8 Classification code: FC  	III	No	Limited quantities: 5 L Tunnel restriction code: (D/E) See below for additional information.
IMDG	UN2924	FLAMMABLE LIQUID, CORROSIVE, N.O.S. (potassium hydroxide;caustic potash, 1-methoxy-2- propanol;monopropylene glycol methyl ether)	Transport hazard class: 3 Label: 3+8 Classification code: FC  	III	No	Limited quantities: 5 L EmS: F-E S-C See below for additional information.
IATA	UN2924	FLAMMABLE LIQUID, CORROSIVE, N.O.S.	Transport hazard class: 3 Label: 3+8	III	No	See below for additional information.

Conforms to Hazardous Products Regulation SOR/2015-17 (as amended by SOR/2022-272)

14.1 UN / ID	14.2 UN proper shipping name	14.3 Hazard class(es)	14.4 PG*	14.5 Env**	Other information:
	(potassium hydroxide;caustic potash, 1-methoxy-2-propanol;monopropylene glycol methyl ether)	Classification code: FC  			

* Packing group

** Environmental hazards

Additional information

This product is within scope of the regulations of transport of dangerous goods.

TDG / See Schedule 1 for any information on special provisions, requirements, or warnings in connection with transport. See part 3, for instructions in writing regarding mitigation of damages in relation to incidents or accidents during transport.

IMDG / See section 3.2.1, for any information on special provisions, requirements, or warnings in connection with transport.

IATA / See Table 4.2 for any information on special provisions, requirements, or warnings in connection with transport.

14.6. Special precautions for user

Not applicable.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

No data available.

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Canadian lists

NDSL:

None of the components are listed

DSL:

benzyl alcohol

1-methoxy-2-propanol;monopropylene glycol methyl ether

potassium hydroxide;caustic potash

D-Glucopyranose, oligomers, decyl octyl glycosides

15.4. Restrictions for application

People under the age of 18 shall not be exposed to this product.

Pregnant women and women breastfeeding must not be exposed to this product. The risk, and possible technical precautions or design of the workplace needed to eliminate exposure, must be considered.

15.5. Demands for specific education

No specific requirements.



Conforms to Hazardous Products Regulation SOR/2015-17 (as amended by SOR/2022-272)

Additional information

If this product is sold in retail, it must be delivered with child-resistant fastening.

15.7. Chemical safety assessment

No

Sources

Hazardous Products Regulation SOR/2015-17 (as amended by SOR/2022-272)

SECTION 16: OTHER INFORMATION

Full text of H-phrases as mentioned in section 3

H226, Flammable liquid and vapour.
H290, May be corrosive to metals.
H302, Harmful if swallowed.
H314, Causes severe skin burns and eye damage.
H318, Causes serious eye damage.
H319, Causes serious eye irritation.
H332, Harmful if inhaled.
H336, May cause drowsiness or dizziness.

The full text of identified uses as mentioned in section 1

None known.

Abbreviations and acronyms

ANSI = American National Standards Institute
ATE = Acute Toxicity Estimate
BCF = Bioconcentration Factor
CAS = Chemical Abstracts Service
DSL = Domestic Substances List
GHS = Globally Harmonized System of Classification and Labelling of Chemicals
HHNOC = Health Hazards Not Otherwise Classified
IARC = International Agency for Research on Cancer
IATA = International Air Transport Association
IMDG = International Maritime Dangerous Goods
LogKow = logarithm of the n-octanol/water coefficient
MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
NDSL = Non-domestic substances list
OECD = Organisation for Economic Co-operation and Development
PBT = Persistent, Bioaccumulative and Toxic
PHNOC = Physical Hazards Not Otherwise Classified
RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail
SCL = A specific concentration limit.
SOR = Statutory Orders and Regulations
STEL = Short-term exposure limits
STOT-RE = Specific Target Organ Toxicity - Repeated Exposure



Conforms to Hazardous Products Regulation SOR/2015-17 (as amended by SOR/2022-272)

STOT-SE = Specific Target Organ Toxicity - Single Exposure

TDG = Transportation of Dangerous Goods

TWA = Time weighted average

UN = United Nations

UVBC = Unknown or variable composition, complex reaction products or of biological materials

VOC = Volatile Organic Compound

vPvB = Very Persistent and Very Bioaccumulative

WHIMS = Workplace Hazardous Materials Information System

Additional information

The classification of the mixture in regard of health hazards is in accordance with the calculation methods given by WHMIS 2022

The classification of the mixture in regard to physical hazards has been based on experimental data.

The safety data sheet is validated by

TD

SDS date: 2026-04-23

Other

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a triangle.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

It is recommended to hand over this safety data sheet to the actual user of the product.

Information in this safety data sheet cannot be used as a product specification.

Country-language: CA-en