



Conforms to Hazardous Products Regulation SOR/2015-17 (as amended by SOR/2022-272)

SAFETY DATA SHEET

Wipeout for Painted Surfaces

SECTION 1: IDENTIFICATION

1.1. Product identifier

Trade name: Wipeout for Painted Surfaces

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture: Paint and varnish remover - Graffiti remover

Uses advised against : None known.

1.3. Details of the supplier of the safety data sheet

Company and address: Off The Walls
754 Francis Road
L7T 4A3 Burlington
Canada
1-905-632-9849

Contact person: Technical Department

E-mail: Technical Department

SDS date: 2026-04-23

SDS Version: 2.0

Date of previous version: 2024-07-18 (1.0)

1.4. Emergency telephone number

613-996-6666, 24 Hours

SECTION 2: HAZARD(S) IDENTIFICATION

Classified as hazardous according to Hazardous Products Regulation SOR/2015-17 (as amended by SOR/2022-272).

2.1. Classification of the substance or mixture

Flam. Liq. 3; H226, Flammable liquid and vapour.
Acute Tox. 4; H302, Harmful if swallowed.
Eye Irrit. 2; H319, Causes serious eye irritation.

2.2. Label elements

Hazard pictogram(s):



Signal word:

Warning

Hazard statement(s):

Flammable liquid and vapour. (H226)
 Harmful if swallowed. (H302)
 Causes serious eye irritation. (H319)

Precautionary statement(s):

General:

If medical advice is needed, have product container or label at hand. (P101)
 Keep out of reach of children. (P102)

▼ *Prevention:*

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. (P210)
 Wash hands thoroughly after handling. (P264)
 Do not eat, drink or smoke when using this product. (P270)
 Wear eye protection. (P280)

Response:

IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell. (P301+P312)
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. (P305+P351+P338)
 If eye irritation persists: Get medical advice/attention. (P337+P313)
 In case of fire: Use water mist/carbon dioxide/alcohol-resistant foam to extinguish. (P370+P378)

Storage:

Store in a well-ventilated place. Keep cool. (P403+P235)

▼ *Disposal:*

Dispose of contents/container in accordance with local regulation. (P501)

Hazardous substances:

2-(2-butoxyethoxy)ethanol; diethylene glycol monobutyl ether
 benzyl alcohol

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substances

Not applicable. This product is a mixture.

3.2. Mixtures

Chemical name	Common name/synonyms	Identifiers	% w/w	Classification	Note

Conforms to Hazardous Products Regulation SOR/2015-17 (as amended by SOR/2022-272)

propan-2-ol;isopropyl alcohol;isopropanol		CAS No.: 67-63-0	25-40%	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H335 (SCL: 100.00 %) STOT SE 3, H336 (SCL: 100.00 %)	
2-(2-butoxyethoxy)ethanol;diethylene glycol monobutyl ether		CAS No.: 112-34-5	25-40%	Acute Tox. 4, H302 Eye Irrit. 2, H319	
benzyl alcohol		CAS No.: 100-51-6	15-25%	Acute Tox. 4, H302 Eye Irrit. 2, H319 Acute Tox. 4, H332	
acetone;propan-2-one;propanone		CAS No.: 67-64-1	1-3%	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 1, HHNOC066	

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

Other information

-

SECTION 4: FIRST-AID MEASURES

4.1. Description of first aid measures

General information:

If breathing is irregular, drowsiness, loss of consciousness or cramps: Call 911 and give immediate treatment (first aid).

Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

Inhalation:

Upon breathing difficulties or irritation of the respiratory tract: Bring the person into fresh air and stay with him/her.

Skin contact:

Upon irritation: rinse with water. In the event of continued irritation, seek medical assistance.

Eye contact:

If in eyes: Flush eyes immediately with plenty of water or isotonic water (20-30 °C) for at least 5 minutes and continue until irritation stops. Remove contact lenses.



Make sure to flush under upper and lower eyelids. If irritation continues, contact a doctor. Continue flushing during transport.

Ingestion: IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell.
Rinse mouth.

Burns: Rinse with water until pain stops then continue to rinse for 30 minutes.

4.2. Most important symptoms and effects, both acute and delayed

Irritation effects: This product contains substances, which may cause irritation upon exposure to skin, eyes or lungs. Exposure may result in an increased absorption potential of other hazardous substances at the area of exposure.

Neurotoxic effects: This product contains organic solvents, which may cause adverse effects to the nervous system. Symptoms of neurotoxicity include: loss of appetite, headache, dizziness, ringing in ears, tingling sensations of skin, sensitivity to the cold, cramps, difficulty in concentrating, tiredness, etc. Repeated exposure to solvents can result in the breaking down of the skin's natural fat layer and may result in an increased absorption potential of other hazardous substances at the area of exposure.

4.3. Indication of any immediate medical attention and special treatment needed

If eye irritation persists: Get medical advice/attention.

Information to medics

Bring this safety data sheet or the label from this product.

SECTION 5: FIRE-FIGHTING MEASURES

5.1. Extinguishing media

Suitable extinguishing media: Alcohol-resistant foam, carbon dioxide, powder, water mist.
Unsuitable extinguishing media: Waterjets should not be used, since they can spread the fire.

5.2. Special hazards arising from the substance or mixture

Flammable liquid and vapour.

In use may form flammable/explosive vapour-air mixture.

Fire will result in dense smoke. Exposure to combustion products may harm your health.

Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

If the product is exposed to high temperatures, e.g. in the event of fire, dangerous decomposition compounds are produced. These are:

Carbon oxides (CO / CO₂)

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact a poison centre in order to obtain further advice. See section 1 "Emergency telephone number".



Conforms to Hazardous Products Regulation SOR/2015-17 (as amended by SOR/2022-272)

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Storages not yet ignited must be cooled by water mist. Remove flammable materials if conditions allow it. Ensure sufficient ventilation.

Ensure adequate ventilation, especially in confined areas.

Contaminated areas may be slippery.

6.2. Environmental precautions

Avoid discharge to lakes, streams, sewers, etc.

Keep unauthorized persons away from the spill

6.3. Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

Wherever possible cleaning should be performed with normal cleaning agents. Avoid use of solvents.

6.4. Reference to other sections

See section 13 "Disposal considerations" on handling of waste.

See section 8 "Exposure controls/personal protection" for protective measures.

SECTION 7: HANDLING AND STORAGE

7.1. ▼ Precautions for safe handling

Ground and bond container and receiving equipment.

Use explosion-proof electrical/lighting/ventilating equipment.

Use non-sparking tools.

Take action to prevent static discharges.

The product should be tested for peroxides before distillation or evaporation and tested for peroxide formation or discarded after 1 year.

Peroxide formation may be present anywhere in the container, including the sides, bottom, exterior and threaded cap. Peroxide formation in ppm concentrations may not be visually observable and must be identified through the use of appropriate testing procedures. If any of the following conditions exist, the material may be explosively unstable and will require stabilization prior to use:

1. Material appears to be degraded and or contaminated.
2. Material appears to be discolored.
3. Deterioration or distortion of storage container.
4. Thermal shock (sunlight).
5. Age of material exceeds recommended storage time.

Avoid contact during pregnancy and while nursing.

Smoking, drinking and consumption of food is not allowed in the work area.

See section 8 "Exposure controls/personal protection" for information on personal protection.



Conforms to Hazardous Products Regulation SOR/2015-17 (as amended by SOR/2022-272)

7.2. Conditions for safe storage, including any incompatibilities

Store in tightly closed containers and store protected from moisture and light. Containers should be dated when opened and tested periodically for the presence of peroxides. Do not exceed storage time limits.

Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

Take action to prevent static discharges.

Must be stored in a cool and well-ventilated area, away from possible sources of ignition.

Recommended storage material: Always store in containers of the same material as the original container.

Storage conditions: Dry, cool and well ventilated

Incompatible materials:
Strong acids
Strong bases
Strong oxidizing agents
Strong reducing agents

7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

ALBERTA

propan-2-ol;isopropyl alcohol;isopropanol
Long term exposure limit (8 hours) (ppm): 200
Long term exposure limit (8 hours) (mg/m³): 492
Short term exposure limit (15 minutes) (ppm): 400
Short term exposure limit (15 minutes) (mg/m³): 984

acetone;propan-2-one;propanone
Long term exposure limit (8 hours) (ppm): 500
Long term exposure limit (8 hours) (mg/m³): 1200
Short term exposure limit (15 minutes) (ppm): 750
Short term exposure limit (15 minutes) (mg/m³): 1800

Occupational Health and Safety Code 2009 Order, Alta Reg 87/2009 (revised in 2018)

BRITISH COLUMBIA

propan-2-ol;isopropyl alcohol;isopropanol
Time-Weighted Average Limit (TWA): 200 ppm
Short-Term Exposure Limit (STEL) / Ceiling Limit (C): 400 ppm
acetone;propan-2-one;propanone
Time-Weighted Average Limit (TWA): 250 ppm



Conforms to Hazardous Products Regulation SOR/2015-17 (as amended by SOR/2022-272)

Short-Term Exposure Limit (STEL) / Ceiling Limit (C): 500 ppm
OHS Regulation Part 5: Chemical Agents and Biological Agents.

ONTARIO

propan-2-ol;isopropyl alcohol;isopropanol
Time-Weighted Average Limit (TWA): 200 ppm
Short-Term Exposure Limit (STEL) / Ceiling Limit (C): 400 ppm
2-(2-butoxyethoxy)ethanol;diethylene glycol monobutyl ether
Time-Weighted Average Limit (TWA): 10 ppm
Annotations:
(IFV) = Inhalable fraction and vapour.

acetone;propan-2-one;propanone
Time-Weighted Average Limit (TWA): 250 ppm
Short-Term Exposure Limit (STEL) / Ceiling Limit (C): 500 ppm
Regulation 833 (Control of Exposure to Biological or Chemical Agents) and Ontario
Regulation 490/09 (Designated Substances)

QUEBEC

propan-2-ol;isopropyl alcohol;isopropanol
Long term exposure limit (8 hours) (ppm): 400
Long term exposure limit (8 hours) (mg/m³): 985
acetone;propan-2-one;propanone
Long term exposure limit (8 hours) (ppm): 500
Long term exposure limit (8 hours) (mg/m³): 1190
Regulation respecting occupational health and safety (Chapter S-2.1, r. 13)

SASKATCHEWAN

propan-2-ol;isopropyl alcohol;isopropanol
Long term exposure limit (8 hours) (ppm): 200
Short term exposure limit (15 minutes) (ppm): 400
acetone;propan-2-one;propanone
Long term exposure limit (8 hours) (ppm): 500
Short term exposure limit (15 minutes) (ppm): 750
The Occupational Health and Safety Regulations, 2020, Chapter S15.1 Reg 10.

8.2. Exposure controls

Compliance with the given occupational exposure limits values should be controlled on a regular basis.

<i>General recommendations:</i>	Smoking, drinking and consumption of food is not allowed in the work area.
<i>Exposure scenarios:</i>	There are no exposure scenarios implemented for this product.
<i>Exposure limits:</i>	Professional users are subjected to the legally set maximum concentrations for occupational exposure. See

	occupational hygiene limit values above.
<i>Appropriate technical measures:</i>	The formation of vapours must be kept at a minimum and below current limit values (see above). Installation of a local exhaust system if normal air flow in the work room is not sufficient is recommended. Ensure eyewash and emergency showers are clearly marked. Apply standard precautions during use of the product. Avoid inhalation of vapours.
<i>Hygiene measures:</i>	In between use of the product and at the end of the working day all exposed areas of the body must be washed thoroughly. Pay special attention to hands, forearms and face.
<i>Measures to avoid environmental exposure:</i>	No specific requirements.

Individual protection measures, such as personal protective equipment

▼ <i>Generally:</i>	No specific requirements.
<i>Respiratory Equipment:</i>	
Use local exhaust or dilution ventilation	
<i>Skin protection:</i>	
Wear chemical protective clothing e.g. gloves, aprons, boots.	
<i>Hand protection:</i>	
Chemical Resistant, impervious gloves	
<i>Eye protection:</i>	
Wear chemical safety goggles and face shield when contact is possible.	

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

<i>Physical state:</i>	Liquid
<i>Colour:</i>	Clear
<i>Odour:</i>	Faint
<i>Odour threshold (ppm):</i>	No data available
<i>pH:</i>	4.6
<i>Density (g/cm³):</i>	-
<i>Relative density:</i>	0.93
<i>Kinematic viscosity:</i>	No data available
<i>Particle characteristics:</i>	No data available

Phase changes

<i>Melting point/Freezing point (°C):</i>	No data available
<i>Softening point/range (°F):</i>	Does not apply to liquids.
<i>Boiling point (°C):</i>	No data available
<i>Vapour pressure:</i>	No data available
<i>Relative vapour density:</i>	No data available
<i>Decomposition temperature (°C):</i>	No data available

Data on fire and explosion hazards

<i>Flash point (°C):</i>	No data available
<i>Flammability (°C):</i>	The material is ignitable.
<i>Auto-ignition temperature (°C):</i>	No data available
<i>Explosion limits (% v/v):</i>	No data available

Solubility

<i>Solubility in water:</i>	No data available
<i>n-octanol/water coefficient (LogKow):</i>	No data available
<i>Solubility in fat (g/L):</i>	No data available

9.2. Other information

<i>Evaporation rate (n-butylacetate = 100):</i>	No data available
<i>Other physical and chemical parameters:</i>	No data available.
<i>Oxidizing properties:</i>	No data available

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

No data available.

10.2. Chemical stability

The product is stable under the conditions, noted in section 7 "Handling and storage".

10.3. Possibility of hazardous reactions

None known.

10.4. Conditions to avoid

Do not expose to any forms of heat (e.g. solar radiation). May lead to excess pressure. Mechanical influences (e.g. Shock, pressure, impact, friction). Fire, sparks or other ignition sources.

10.5. Incompatible materials

Strong acids



Conforms to Hazardous Products Regulation SOR/2015-17 (as amended by SOR/2022-272)

Strong bases
Strong oxidizing agents
Strong reducing agents

10.6. ▼ Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Acute toxicity

Harmful if swallowed.

Skin corrosion/irritation

Based on available data, the classification criteria are not met.

Serious eye damage/irritation

Causes serious eye irritation.

Respiratory sensitisation

Based on available data, the classification criteria are not met.

Skin sensitisation

Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Long term effects

Irritation effects: This product contains substances, which may cause irritation upon exposure to skin, eyes or lungs. Exposure may result in an increased absorption potential of other hazardous substances at the area of exposure.

Neurotoxic effects: This product contains organic solvents, which may cause adverse effects to the nervous system. Symptoms of neurotoxicity include: loss of appetite, headache, dizziness, ringing in ears, tingling sensations of skin, sensitivity to the cold, cramps,

difficulty in concentrating, tiredness, etc. Repeated exposure to solvents can result in the breaking down of the skin's natural fat layer and may result in an increased absorption potential of other hazardous substances at the area of exposure.

Other information

propan-2-ol;isopropyl alcohol;isopropanol has been classified by IARC as a group 3 carcinogen.

SECTION 12: ECOLOGICAL INFORMATION

12.1. ▼ Toxicity

Based on available data, the classification criteria are not met.

12.2. Persistence and degradability

Based on available data, the classification criteria are not met.

12.3. Bioaccumulative potential

Based on available data, the classification criteria are not met.

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification.

12.6. Other adverse effects

None known.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste treatment methods


acetone;propan-2-one;propanone is listed with EPA Hazardous Waste Number: U002

Specific labelling



Contaminated packing

Packaging containing residues of the product must be disposed of similarly to the product.

SECTION 14: TRANSPORT INFORMATION

	14.1 UN / ID	14.2 UN proper shipping name	14.3 Hazard class(es)	14.4 PG*	14.5 Env**	Other information:
TDG	UN1993	FLAMMABLE LIQUID, N.O.S. (propan-2-ol;isopropyl alcohol;isopropanol)	Transport hazard class: 3 	II	No	See below for additional information.

Conforms to Hazardous Products Regulation SOR/2015-17 (as amended by SOR/2022-272)

	14.1 UN / ID	14.2 UN proper shipping name	14.3 Hazard class(es)	14.4 PG*	14.5 Env**	Other information:
IMDG	UN1993	FLAMMABLE LIQUID, N.O.S. (propan-2-ol;isopropyl alcohol;isopropanol)	Transport hazard class: 3 	II	No	See below for additional information.
IATA	UN1993	FLAMMABLE LIQUID, N.O.S. (propan-2-ol;isopropyl alcohol;isopropanol)	Transport hazard class: 3 	II	No	See below for additional information.

* Packing group

** Environmental hazards

▼ Additional information

This product is within scope of the regulations of transport of dangerous goods.

TDG / See Schedule 1 for any information on special provisions, requirements, or warnings in connection with transport. See part 3, for instructions in writing regarding mitigation of damages in relation to incidents or accidents during transport.

IMDG / See section 3.2.1, for any information on special provisions, requirements, or warnings in connection with transport.

IATA / See Table 4.2 for any information on special provisions, requirements, or warnings in connection with transport.

14.6. Special precautions for user

Not applicable.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

No data available.

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. ▼ Canadian lists

▼ *NDSL*:

None of the components are listed

▼ *DSL*:

propan-2-ol;isopropyl alcohol;isopropanol
2-(2-butoxyethoxy)ethanol;diethylene glycol monobutyl ether
benzyl alcohol
acetone;propan-2-one;propanone

15.4. Restrictions for application

Pregnant women and women breastfeeding must not be exposed to this product. The risk, and possible technical precautions or design of the workplace needed to eliminate exposure, must be considered.



Conforms to Hazardous Products Regulation SOR/2015-17 (as amended by SOR/2022-272)

15.5. Demands for specific education

No specific requirements.

Additional information

Not applicable.

15.7. Chemical safety assessment

No

Sources

Hazardous Products Regulation SOR/2015-17 (as amended by SOR/2022-272)

SECTION 16: OTHER INFORMATION

Full text of H-phrases as mentioned in section 3

H225, Highly flammable liquid and vapour.

H302, Harmful if swallowed.

H319, Causes serious eye irritation.

H332, Harmful if inhaled.

H335, May cause respiratory irritation.

H336, May cause drowsiness or dizziness.

Repeated exposure may cause skin dryness or cracking, Repeated exposure may cause skin dryness or cracking.

The full text of identified uses as mentioned in section 1

None known.

Abbreviations and acronyms

ANSI = American National Standards Institute

ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

CAS = Chemical Abstracts Service

DSL = Domestic Substances List

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

HHNOC = Health Hazards Not Otherwise Classified

IARC = International Agency for Research on Cancer

IATA = International Air Transport Association

IMDG = International Maritime Dangerous Goods

LogKow = logarithm of the n-octanol/water coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

NDSL = Non-domestic substances list

OECD = Organisation for Economic Co-operation and Development

PBT = Persistent, Bioaccumulative and Toxic

PHNOC = Physical Hazards Not Otherwise Classified

RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail

SCL = A specific concentration limit.



Conforms to Hazardous Products Regulation SOR/2015-17 (as amended by SOR/2022-272)

SOR = Statutory Orders and Regulations
STEL = Short-term exposure limits
STOT-RE = Specific Target Organ Toxicity - Repeated Exposure
STOT-SE = Specific Target Organ Toxicity - Single Exposure
TDG = Transportation of Dangerous Goods
TWA = Time weighted average
UN = United Nations
UVBC = Unknown or variable composition, complex reaction products or of biological materials
VOC = Volatile Organic Compound
vPvB = Very Persistent and Very Bioaccumulative
WHIMS = Workplace Hazardous Materials Information System

Additional information

The classification of the mixture in regard of health hazards is in accordance with the calculation methods given by WHMIS 2022
The classification of the mixture in regard to physical hazards has been based on experimental data.

The safety data sheet is validated by

TD

SDS date: 2026-04-23

Other

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a triangle.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

It is recommended to hand over this safety data sheet to the actual user of the product.

Information in this safety data sheet cannot be used as a product specification.

Country-language: CA-en